

# Eaton 5E550I

Catalog Number: 5E550I

Eaton 5E Gen2 UPS IEC, 550 VA, 300W, Input: C14, Outputs: (4) C13, Tower

## General specifications

Product Name	Catalog Number
Eaton 5E Gen2 UPS	5E550I
Product Length/Depth	Product Height
288 mm	148 mm
Product Width	Product Weight
100 mm	3.75 kg
Warranty	Compliances
2 year	CB
	LVD Directive
	EMC Directive
	RoHS Directive
	Packaging Directive
	WEEE Directive
	Batteries Directive



## Certifications

IEC/EN 62040-1  
IEC/EN 62040-2  
CE  
EAC  
UKCA  
Cm  
Ukr  
IEC/EN 62040-3

## Secondary frequency - max

60 Hz

## Wattage

300W

## Form factor

Tower

## Includes network card

No

## Input connection

C14

## Input voltage - min

140 V

## Output voltage - max

257 V

## Secondary frequency - min

50 Hz

## Battery type

Sealed, lead-acid

## Efficiency

95

## Special features

Automatic Voltage Regulation (AVR)

Saves space with a compact tower design

## Construction type

Free standing model

## Output voltage - min

195 V

## Color

Black

## Extended battery capability

No

## Output voltage range

195-257 V

## Topology

Line-interactive

#### Surge protection

Yes

#### Input nominal voltage

230V default (220/230/240V)

#### Input frequency range

45-63 Hz

#### Internal bypass

No

#### Input voltage - max

300 V

#### Voltage type

AC

#### Phase (output)

1

#### Battery management

Automatic battery test, deep-discharge protection, cold-start capable

#### Auto shutdown function

No

#### Number of Outputs C13

4

#### Operating temperature - min

0 °C

#### VA rating

550 VA

#### Potential free switch contact

No

#### Receptacle

(4) C13

#### Phase (input)

1

#### Package contents

(2) IEC-IEC output cables

Quick start

Safety instructions

#### Feed type

1

## Runtime graph

[View runtime graph](#)

## User interface

LEDs

## Battery quantity

1

## Operating temperature - max

40 °C

## Voltage

230V

## Hot swap power

No

## Temperature range

0° to 40°C (32° to 104°F)

## Ethernet interface

No

## Relative humidity

0-90% non-condensing

## Output apparent power

550 VA

## Rack mounting kit

No

## Output frequency

50/60 Hz

## Type of interface

None

## Primary frequency - min

45 Hz

## Battery rating

12 V / 4.5 Ah

## Type

UPS

## Output nominal voltage

230V

## Expansion slots

No

## Input voltage range

140-300 V

Nominal frequency

50/60 Hz

Primary frequency - max

63 Hz



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2023 Eaton. Všechna  
práva vyhrazena.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)